



Interactive Board - Enterprise Series

Bring life to your classroom environment with Globus Interactive Board

MODEL: IR 82D

IR 82D

Application Areas

Schools - Colleges - Universities

Corporate Offices - Meeting Rooms - Training Rooms

Huddle Rooms - Conference Rooms

Interactive Board

Technical Specifications

Model	IR 82D
Board Size	82"
Technology	Infrared
Board Surface	Scratch resistant ceramic surface for smooth writing and exceptional erasability, possible to fully erase the marking of Whiteboard marker pen on the surface using ethanol.
Aspect Ratio	4:3
Touch Input	Touch sensitive (Finger / Stylus / Pen)
Touch Points	6 point writing, 10 point touch
Resolution	32767 x 32767
Scan Rate	125 dots / second
Response Time	4 ms
Accuracy	1 mm
Hot Keys	Available on both sides of the board
Interface	USB (Type A-B)
Driver Support (OS)	Windows XP, Vista, Win 7, Win 8, Win 10, MAC & Linux
Software Features	Annotation Features like draw, choose, pens, annotate, erase, color, shapes, sizes, text, edit, fonts, stamp, move, capture picture, video, save, rotate, undo, image gallery, print, floating keyboard, background etc.
Interactive Application	Capability to connect up to 30 interactive pads without cable
Collaboration	Pads, Panel, Visualizer, Board work in a collaborative environment
Power Consumption	< 0.5W (Power supply through USB)
Operating Temperature	0° to 40° C, 80% RH at 40° C
Mounting Options	Wall Mount (Standard)/ Floor Mount (Optional)
Accessories	USB Cable, User Manual, Stylus Holder with 2 Stylus, Wall Mount Kit
Special Features	USB Powered Scratch resistant surface Infra-red Multi-Touch technology



Hot Keys
on both Sides

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.