





Dazzle Series <mark>Joystick Controller</mark> Model: GIL Kbd

GIL Kbc



Educational Institutes, Hospital, Offices

Shops, Malls and other market places

Airport, Railway stations etc.

Joystick Controller

Applications

Model: GIL Kbd

Special Features

- Three Dimensional Joystick Control of PTZ Functions
- Vector-solving, with twisting, return to-center head
- Direct Mode,Network Mode
- Auxiliary Functions
- Network video server
- On-Screen Menu & User Operation Procedure Tips
- External Wi-Fi (Optional)

Keyboard Key panel	Electromechanical
Resolution	LCD, 75.2mm x 33.85mm
Keyboard Connector	RJ-45, RS232, RS485, RS422, USB
Direct Mode	Interface: RS232/RS485
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol
Power Supply	Power adapter, input 100V-240V 50Hz I 60Hz, output DC12V/1000mA
Baud Rate	2400/4800/9600
Power Consumption	5W
Working Temperature	-10- 55 □C
Atmosphere Pressure	86kpa-106kpa

Technical Specifications

*Due to continuous product development, the specifications may change without prior notice. **Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301 ↓ 0120-4051700/800 🖶 0120-4051827 🖂 info@globusinfocom.com □ For Sales: 0 85888 39434